

AD-A241 584



2

NAVSWC TR 91-323


HOMOLOGY AND HYPERGRAPH ACYCLICITY: A COMBINATORIAL INVARIANT FOR HYPERGRAPHS

**BY A.D. PARKS
STRATEGIC SYSTEMS DEPARTMENT**

AND

**S.L. LIPSCOMB
MARY WASHINGTON COLLEGE**

JUNE 1991



Approved for public release; distribution is unlimited.

91-12652



NAVAL SURFACE WARFARE CENTER

Dahlgren, Virginia 22448-5000 • Silver Spring, Maryland 20903-5000

91 10 7 048

NAVSWC TR 91-323

**HOMOLOGY AND HYPERGRAPH ACYCLICITY:
A COMBINATORIAL INVARIANT
FOR HYPERGRAPHS**

**BY A.D. PARKS
STRATEGIC SYSTEMS DEPARTMENT**

AND

**S.L. LIPSCOMB
MARY WASHINGTON COLLEGE**

JUNE 1991

Approved for public release; distribution is unlimited.

**NAVAL SURFACE WARFARE CENTER
Dahlgren, Virginia 22448-5000 • Silver Spring, Maryland 20903-5000**

FOREWORD

This report describes certain theoretical results obtained from work performed jointly in the Strategic Systems (K) Department at the Naval Surface Warfare Center (NAVSWC) and in the Department of Mathematics at Mary Washington College under the auspices of an independent research grant entitled "A Category Theoretic Approach to Relational Database Schemes."

This report has been reviewed and approved by Ted Sims, Space Sciences Branch Head, and James L. Sloop, Space and Surface Systems Division Head.

Approved by:

R. L. Schmidt
R. L. SCHMIDT, Head
Strategic Systems Department



Accession For	
NTIS GRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist	Avail and/or Special
A-1	

CONTENTS

	<u>Page</u>
INTRODUCTION.....	1
DEFINITIONS.....	1
PRELIMINARY LEMMAS	2
ACYCLIC HYPERGRAPHS	5
EXAMPLES AND h -ACYCLIC HYPERGRAPHS	7
REMARKS	8
REFERENCES	9
DISTRIBUTION.....	(1)

INTRODUCTION

Because of their utility as relational database scheme models, certain classes of *acyclic* hypergraphs are important in a practical sense. These classes exhibit a nonreversible hierarchy, i.e., $\text{Berge-acyclicity} \Rightarrow \gamma\text{-acyclicity} \Rightarrow \beta\text{-acyclicity} \Rightarrow \alpha\text{-acyclicity}$ [1,2,4]. From a purely graph-theoretic standpoint, these degrees of acyclicity can be characterized [3] by parallel degrees of chordality of simple graphs.

Here, the approach depends on a natural association of an abstract simplicial complex $\mathcal{S}_{\mathcal{H}}$ with a hypergraph \mathcal{H} , i.e., edges and their pairwise set intersections determine, respectively, abstract simplices and their pairwise common faces. We then choose a geometrical realization $K_{\mathcal{H}}$ of $\mathcal{S}_{\mathcal{H}}$ and the new invariant $\chi(\mathcal{H})$ is defined as the Euler number $\chi(K_{\mathcal{H}})$ [7, p.124].

A new invariant for simple graphs is obtained by coupling the bijection $G \mapsto f(G)$ [1,3] (a graph G maps to the hypergraph $f(G)$ of its maximal cliques) with the hypergraph invariant. We calculate that χ has value one for hypergraphs that are connected α -acyclic by applying the Mayer-Vietoris sequence to show that the homology of the associated complex $K_{\mathcal{H}}$ is trivial — several corollaries immediately follow.

This construction is analogous to the well known construction [6] of the invariant $p = |V| - \sum_i^m (|E_i| - 1)$ for the class of Berge-acyclic ($\Rightarrow \alpha$ -acyclic) hypergraphs. In the Berge case, a bipartite graph K_1 (a one-dimensional complex) is associated with a hypergraph and then the Euler number $\chi(K_1)$ is calculated. Here, a complex $K_{\mathcal{H}}$ (of dimension ≥ 1) is associated with a hypergraph \mathcal{H} and then the Euler number $\chi(K_{\mathcal{H}})$ is calculated. We show (1) analogous to the Berge case, a hypergraph \mathcal{H} is connected α -acyclic \Rightarrow the complex $K_{\mathcal{H}}$ is acyclic $\Rightarrow \chi(K_{\mathcal{H}}) = 1$; but (2) unlike the Berge case, these implications cannot (in general) be reversed. As a result of this, a new degree of hypergraph acyclicity, which we call *h-acyclicity*, is introduced and we have: \mathcal{H} is *h-acyclic* $\Leftrightarrow K_{\mathcal{H}}$ is homologically acyclic.

DEFINITIONS

A *hypergraph* \mathcal{H} is a pair $(\mathcal{N}, \mathcal{E})$, where \mathcal{N} is a finite set of vertices and \mathcal{E} is a set of (hyper)edges which are nonempty subsets of \mathcal{N} . A hypergraph is *reduced* if no edge is a subset of another edge. It will be assumed here that all hypergraphs are reduced. A hypergraph is α -acyclic when it has the *running intersection property*, i.e., there is an ordering (e_1, \dots, e_n) of its edges such that for each i , $2 \leq i \leq n$, there is a $j_i < i$ such that $e_i \cap (\cup_{k < i} e_k) \subseteq e_{j_i}$. Further, a hypergraph has the *nonempty*

running intersection property when each of the $n - 1$ intersections $e_i \cap (\cup_{k < i} e_k)$ is not empty. For hypergraphs, the nonempty running intersection property clearly implies both connectedness and α -acyclicity; and the converse follows by obtaining a separation when one of the $n - 1$ intersections is empty. Indeed, if p is the number of connected pieces and q is the number of empty intersections $e_i \cap (\cup_{k < i} e_k)$, then $p = q + 1$.

Let G be a loopless, undirected simple graph with vertex set V . Then G is *chordal* if every cycle of length ≥ 4 has a *chord*. A *clique* of G is a complete subgraph of G . We let $\mathcal{M}(G)$ denote the family of subsets of V that induce maximal cliques of G . The correspondence $\mathcal{M} = \mathcal{M}(G)$ induces the bijection f which associates with each simple graph G the hypergraph $f(G) = (V, \mathcal{M})$ [1,3].

If S is a finite set, then the *closure* of S , $Cl(S)$, is the family of nonempty subsets of S . The *closure* of \mathcal{H} , $Cl(\mathcal{H})$, is the union of the closures of its edges, i.e., $Cl(\mathcal{H}) = \bigcup_{E \in \mathcal{H}} Cl(E)$. The number of sets of cardinality k in $Cl(\mathcal{H})$, $Cl(\mathcal{M}(G))$ is denoted h_k , g_k . Finally, the maximum k for which $h_k \neq 0$, $g_k \neq 0$ is denoted $\overline{\mathcal{H}}$, $\overline{\mathcal{M}}$.

Let $\{a_0, \dots, a_k\}$ be a set of *geometrically independent points* in R^n . The k -*simplex* (or *simplex*) σ^k spanned by $\{a_0, \dots, a_k\}$ is the set of points x in R^n for which there exist nonnegative real numbers $\lambda_0, \dots, \lambda_k$ such that $x = \sum_{i=0}^k \lambda_i a_i$ and $\sum_{i=0}^k \lambda_i = 1$. In this case, $\{a_0, \dots, a_k\}$ is called the *vertex set* of σ^k . A *face* of σ^k is any simplex spanned by a nonempty subset of $\{a_0, \dots, a_k\}$. A *finite geometrical simplicial complex* (or *complex*) K is a finite set theoretic union of simplices such that: (1) every face of a simplex of K is in K ; and (2) the nonempty intersection of any two simplices of K is a common face of each. Here we deal only with finite simplicial complexes. Thus, the dimension of K is the largest positive integer m such that K contains an m -simplex. The *vertex scheme* of K is the family of all vertex sets which span the simplices of K . If $\{L_i\}$ is a family of subcomplexes of K , then $\cup_i L_i$ and $\cap_i L_i$ (when not empty) are subcomplexes of K .

A *finite abstract simplicial complex* (or *abstract complex*) is a finite family \mathcal{S} of finite nonempty sets such that if A is in \mathcal{S} , then so is every nonempty subset of A . Accordingly, the vertex scheme of a complex is an abstract complex; and when nonempty, a finite union of set closures and a finite intersection of set closures are abstract complexes.

Two abstract complexes \mathcal{S} and \mathcal{T} are isomorphic when a bijection ϕ from the vertex set of \mathcal{S} onto the vertex set of \mathcal{T} satisfies $\{a_0, \dots, a_k\} \in \mathcal{S}$ if, and only if, $\{\phi(a_0), \dots, \phi(a_k)\} \in \mathcal{T}$. Every abstract complex \mathcal{S} is isomorphic to the vertex scheme of some geometrical simplicial complex K . The complex K is then called a *geometrical realization* of \mathcal{S} and is uniquely determined (up to linear isomorphism). We denote an isomorphism between \mathcal{S} and the vertex scheme of K by $\mathcal{S} \cong K$. An *edge* $e = \{u, v\} \in \mathcal{S}$ is a doubleton subset contained in \mathcal{S} . A distinct pair of vertices u, v of \mathcal{S} are *path connected* if there is an alternating sequence $u\{u, x_1\}x_1\{x_1, x_2\} \dots \{x_n, v\}v$ of vertices and edges of \mathcal{S} . The abstract complex \mathcal{S} is *connected* when either \mathcal{S} has only one vertex, or all pairs of its vertices are path

connected. If S is connected, so is any geometrical realization of S .

To each simplicial complex K there corresponds a chain complex, i.e., for $p = 0, 1, 2, \dots$ there are abelian groups $C_p(K)$ and homomorphisms $\partial_{p+1} : C_{p+1}(K) \rightarrow C_p(K)$. If K is finite and $\eta_p(K)$ is the number of p -simplices in K , then the rank of $C_p(K)$ is $\eta_p(K)$, i.e., $C_p(K)$ is isomorphic " \cong " to the direct sum " \oplus " of $\eta_p(K)$ copies of the additive group of integers Z . The p^{th} homology group of K , $H_p(K) = \ker \partial_p / \text{im } \partial_{p+1}$, is finitely generated. The rank of $H_p(K)$ is the p^{th} betti number $b_p(K)$. If K is connected, then $H_0(K) \cong Z$. K is homologically trivial or homologically acyclic if $H_p(K) \cong 0$ whenever $p > 0$ and $H_0(K) \cong Z$. The complex of a simplex is homologically trivial.

PRELIMINARY LEMMAS

Several lemmas are required. The first three are well known and are repeated here for completeness. The fourth is due to DAtri, et al [3].

Lemma 1 ([7, p. 142]) (Mayer-Vietoris). *Let L be a complex with subcomplexes K and L' such that $L = K \cup L'$. Then there is an exact sequence*

$$\dots \rightarrow H_p(K \cap L') \rightarrow H_p(K) \oplus H_p(L') \rightarrow H_p(L) \rightarrow H_{p-1}(K \cap L') \rightarrow \dots$$

Lemma 2 ([8, p. 254]). *Let A be an abelian group, F a free abelian group, and $\theta : A \rightarrow F$ be onto. Then $A \cong \ker \theta \oplus F$.*

Lemma 3 ([5, p. 242]) (Euler-Poincaré). *If K is a complex of dimension m , then*

$$\sum_{p=0}^m (-1)^p \eta_p(K) = \sum_{p=0}^m (-1)^p b_p(K). \quad (1)$$

Lemma 4 ([3, p. 273]). *A graph G is chordal if, and only if, $f(G)$ is α -acyclic.*

To obtain the new hypergraph invariant we start with the hypergraph $\mathcal{H} = (\mathcal{N}, \mathcal{E})$. Intuitively, we wish to make each edge $E \in \mathcal{E}$ into an abstract simplex — this amounts to considering the family $\mathcal{C}\ell(E)$. And intuitively, we wish to make \mathcal{H} into an abstract simplicial complex — this amounts to considering the family $\mathcal{C}\ell(\mathcal{H})$. We then associate $\mathcal{C}\ell(\mathcal{H})$ with one of its geometric realizations $K = K(\mathcal{C}\ell(\mathcal{H}))$. The new hypergraph invariant can then be defined as the Euler-Poincaré invariant of this simplicial complex K , i.e., the Euler number or value of either the right or left side of (1). Similarly, the new invariant for graphs G can be defined as the Euler-Poincaré invariant of the simplicial complex $K(\mathcal{C}\ell(f(G)))$. Consequently, the first step in constructing the hypergraph invariant involves the operator $\mathcal{C}\ell$. The next lemma provides the key properties of $\mathcal{C}\ell$. The proof is straightforward and is therefore omitted.

Lemma 5. Let $\{S_i | i \in I\}$ be a collection of nonempty finite sets. Then the following statements are true.

- (1) $A \subset B \Leftrightarrow Cl(A) \subset Cl(B)$;
- (2) $\cap_i Cl(S_i) = Cl(\cap_i S_i)$;
- (3) $\cup_i Cl(S_i) \subset Cl(\cup_i S_i)$;
- (4) $\emptyset \neq A \cap B \Leftrightarrow \emptyset \neq Cl(A) \cap Cl(B)$; and
- (5) $\emptyset \neq A \Leftrightarrow \emptyset \neq Cl(A)$.

Lemma 6. The operator Cl preserves the (nonempty) running intersection property. That is, if (S_1, \dots, S_n) has the (nonempty) running intersection property, then the ordered set $(Cl(S_1), \dots, Cl(S_n))$ has the (nonempty) running intersection property.

PRCOF: Write $S_i \cap (\cup_{k < i} S_k) = \cup_{k < i} (S_i \cap S_k)$. Then each addend on the right is a subset of S_{j_i} , and by (1) and (2) of Lemma 5 each addend $(Cl(S_i) \cap Cl(S_k))$ of the corresponding union is a subset of $Cl(S_{j_i})$. Thus, the operator Cl preserves the running intersection property. To see that the "nonempty condition" is also preserved by Cl , note that if one of the addends $S_i \cap S_k$ is not empty, then by (4) Lemma 5 the corresponding addend $Cl(S_i) \cap Cl(S_k)$ must also be nonempty. Thus, Cl also preserves each of the $n - 1$ "nonempty conditions." ■

Lemma 7. Let (S_1, \dots, S_n) have the running intersection property. If $S' = S_i \cap (\cup_{k < i} S_k)$, then

$$Cl(S') = Cl(S_i) \cap (\cup_{k < i} Cl(S_k)).$$

PROOF: Again, write $S' = S_i \cap (\cup_{k < i} S_k) = \cup_{k < i} (S_i \cap S_k)$. Then, for a nonempty set A , applications of Lemma 5 and the definition of Cl can justify the following statements and finish the proof:

$$\begin{aligned} A \in Cl(S') &\Leftrightarrow A \subset S' \Leftrightarrow A \subset S_i \cap S_k \text{ for some } k < i \\ &\Leftrightarrow A \in Cl(S_i \cap S_k) \text{ for some } k < i \\ &\Leftrightarrow A \in \cup_{k < i} Cl(S_i \cap S_k) \\ &\Leftrightarrow A \in \cup_{k < i} (Cl(S_i) \cap Cl(S_k)) \\ &\Leftrightarrow A \in Cl(S_i) \cap (\cup_{k < i} Cl(S_k)). \quad \blacksquare \end{aligned}$$

Lemma 8. Let $\mathcal{H} = (\mathcal{N}, \mathcal{E})$ be a hypergraph. Then $S_{\mathcal{H}} = Cl(\mathcal{H}) = \bigcup_{E \in \mathcal{E}} Cl(E)$ is the abstract simplicial complex associated with \mathcal{H} . Let K be a geometrical realization of $S_{\mathcal{H}}$. Then $K_{\mathcal{H}} = K$ is called a geometrical simplicial complex associated with \mathcal{H} . If (E_1, \dots, E_n) is an ordering of \mathcal{E} that satisfies the nonempty running intersection property,

- (1) then let the simplex K_i of $K_{\mathcal{H}}$ correspond to the simplex $Cl(E_i)$ of $S_{\mathcal{H}}$;

- (2) then the subcomplex L_i of $K_{\mathcal{H}}$ corresponding to the subcomplex $\cup_{k < i} C\ell(E_k)$ of $\mathcal{S}_{\mathcal{H}}$ is connected; and
 (3) then the simplex $K_i \cap L_i$ of $K_{\mathcal{H}}$ necessarily corresponds to the simplex $C\ell(E_i) \cap (\cup_{k < i} C\ell(E_k))$ of $\mathcal{S}_{\mathcal{H}}$.

PROOF: Since $\mathcal{S}_{\mathcal{H}} \cong K_{\mathcal{H}}$, we only need to show (1') $C\ell(E_i)$ is a simplex of $\mathcal{S}_{\mathcal{H}}$; (2') $\cup_{k < i} C\ell(E_k)$ is a connected subcomplex of $\mathcal{S}_{\mathcal{H}}$; and (3') $C\ell(E_i) \cap (\cup_{k < i} C\ell(E_k))$ is nonempty and a simplex of $\mathcal{S}_{\mathcal{H}}$. But (1') follows from $\mathcal{S}_{\mathcal{H}} = \bigcup_{E \in \mathcal{E}} C\ell(E)$ and the definition of an abstract simplex; (2') follows from an induction argument on $i \geq 2$ and the "nonempty condition"

$$\emptyset \neq C\ell(E_i) \cap (\cup_{k < i} C\ell(E_k));$$

and (3') follows from this "nonempty condition," Lemma 7, and the definition of an abstract simplex. ■

ACYCLIC HYPERGRAPHS

With the terminology developed above, we can prove:

Theorem 9. *If \mathcal{H} is a connected α -acyclic hypergraph, then any associated geometrical simplicial complex $K_{\mathcal{H}}$ is homologically trivial.*

PROOF: Using the notation of Lemma 8, we let $i \in \{2, \dots, n\}$ be fixed and consider the simplices $K_i \cap L_i$ and $K_i \cup L_i = L_{i+1}$. From Lemma 1 there is an exact sequence

$$\dots \rightarrow H_p(K_i \cap L_i) \rightarrow H_p(K_i) \oplus H_p(L_i) \rightarrow H_p(L_{i+1}) \rightarrow H_{p-1}(K_i \cap L_i) \rightarrow \dots$$

Some of these groups are easily calculated. For example, since K_i and $K_i \cap L_i$ are simplices,

$$H_p(K_i) \cong H_p(K_i \cap L_i) \cong 0 \quad (p \geq 1) \quad (2)$$

and

$$H_0(K_i) \cong H_0(K_i \cap L_i) \cong \mathbb{Z}. \quad (3)$$

Accordingly, substitution of (2) and (3) into the Mayer-Vietoris sequence induces two relevant exact sequences:

$$0 \rightarrow H_p(L_i) \rightarrow H_p(L_{i+1}) \rightarrow 0 \quad (p \geq 2) \quad (4)$$

and

$$\dots \rightarrow 0 \rightarrow H_1(L_i) \xrightarrow{\delta} H_1(L_{i+1}) \xrightarrow{\nu} \mathbb{Z} \xrightarrow{\pi} \mathbb{Z} \oplus H_0(L_i) \xrightarrow{\theta} H_0(L_{i+1}) \rightarrow 0 \rightarrow \dots \quad (5)$$

Since $i \geq 2$ is arbitrary, the exactness of (4) yields

$$H_p(L_2) \cong H_p(L_3) \cong \dots \cong H_p(L_{n+1}) = H_p(K). \quad (p \geq 2) \quad (6)$$

For $p \geq 2$ the first group $H_p(L_2)$ in (6) is 0 since L_2 is a simplex. Whence, (6) shows

$$H_p(K) = 0 \quad (p \geq 2). \quad (7)$$

To calculate the homology for K in dimension $p = 1$, we use the sequence (5): The exactness of (5) insures θ is surjective. Then Lemma 2, where $H_0(L_{i+1})$ free abelian and θ onto, and the exactness of (5) give

$$Z \oplus H_0(L_i) \cong \ker \theta \oplus H_0(L_{i+1}) = \text{im } \pi \oplus H_0(L_{i+1}). \quad (8)$$

From Lemma 8 L_i, L_{i+1} are connected. Since $H_0(L_i) \cong Z \cong H_0(L_{i+1})$ we substitute Z into (8) and obtain

$$Z \oplus Z \cong \text{im } \pi \oplus Z. \quad (9)$$

From (9) $\text{im } \pi \cong Z$ and hence π is injective ($\ker \pi = 0$). So, the exactness of (5) at Z yields an exact sequence (4) for $p = 1$:

$$0 \longrightarrow H_1(L_i) \longrightarrow H_1(L_{i+1}) \longrightarrow 0 \quad (p = 1). \quad (10)$$

Therefore, since $i \geq 2$ is arbitrary, (10) shows that (6) also holds for $p = 1$. Repeating the argument above, for $p = 1$ the first group $H_p(L_2)$ in (6) is 0 since L_2 is a simplex. Ergo, (6) for $p = 1$ assigns

$$H_1(K) = 0. \quad (11)$$

Consequently, $L_{n+1} = K$ connected, (7), and (11) show K is homologically trivial.■

Corollary 10. *If \mathcal{H} is a connected α -acyclic hypergraph, then*

$$\sum_{k=1}^{\overline{\mathcal{H}}} (-1)^{k-1} h_k = 1. \quad (12)$$

PROOF: Because of the one-one correspondence between the $k - 1$ dimensional simplices of $K = K_{\mathcal{H}}$ and the sets of size k in the family $\mathcal{S}_{\mathcal{H}} = \mathcal{Cl}(\mathcal{H})$ we have $\dim(K) = \overline{\mathcal{H}} - 1$ and $\eta_{k-1}(K) = h_k$. The validity of the equation (12) now follows from these observations, Theorem 1, and the appropriate substitutions in the Euler-Poincaré formula (1).■

Corollary 11. *If G is a connected chordal graph, then*

$$\sum_{k=1}^{\overline{\mathcal{M}}} (-1)^{k-1} g_k = 1. \quad (13)$$

PROOF: First, we apply Lemma 4: Let the connected chordal graph G correspond to the connected α -acyclic hypergraph $f(G) = \mathcal{H}$. Observe that $g_k = h_k$ (and hence $\overline{\mathcal{M}} = \overline{\mathcal{H}}$). The validity of (13) is a consequence of these observations and appropriate substitutions in (12).■

Corollary 12. *If \mathcal{H} is an α -acyclic hypergraph, then $\chi(\mathcal{H})$ is the number p of components of \mathcal{H} .*

PROOF: Let $\{\mathcal{H}_t\}$ be the set of connected components of \mathcal{H} ; let $\{K_t\}$ be a pairwise disjoint set of associated geometrical realizations, i.e., for each t , K_t is associated with \mathcal{H}_t . Let $K_{\mathcal{H}} = \bigvee_t K_t$ be the disjoint union of the K_t . Furthermore, let (E_1, \dots, E_n) be an ordering of the edges of \mathcal{H} that satisfies the running intersection property and, for each t , let V_t denote the vertex set of the component \mathcal{H}_t . Then the induced ordering of the nonempty sets in the list $(E_1 \cap V_t, \dots, E_n \cap V_t)$ is an ordering of the edges of \mathcal{H}_t that satisfies the nonempty running intersection property. So, according to Theorem 9, $\chi(\mathcal{H}_t) = 1$ for each component \mathcal{H}_t . To finish the proof recall that the p^{th} betti number $b_p(K_{\mathcal{H}})$ of a disjoint union $K_{\mathcal{H}} = \bigvee_t K_t$ of complexes K_t is the sum $\sum_t b_p(K_t)$ of the betti numbers $b_p(K_t)$. ■

EXAMPLES AND h -ACYCLIC HYPERGRAPHS

Analogous to the Berge case, we have (by Theorem 9):

$$\mathcal{H} \text{ connected } \alpha\text{-acyclic} \Rightarrow K_{\mathcal{H}} \text{ homologically acyclic} \Rightarrow \chi(K_{\mathcal{H}}) = 1. \quad (14)$$

Unlike the Berge case however, the two implications in (14) cannot (in general) be reversed. For sure, two simple examples suffice to show no two of the three statements in (14) are equivalent.

First, for \mathcal{H} connected, we see

$$\mathcal{H} \text{ connected } \alpha\text{-acyclic} \not\Rightarrow K_{\mathcal{H}} \text{ homologically acyclic} \quad (15)$$

by considering the hypergraph $\mathcal{H} = (\mathcal{N}, \mathcal{E})$ with four vertices, 1, 2, 3, x , and three edges $\{1, 2, x\}$, $\{1, 3, x\}$, $\{2, 3, x\}$. Indeed, not one of the six possible orderings of \mathcal{E} satisfies the running intersection property while $K_{\mathcal{H}}$ is isomorphic to a triangulation of a closed 2-disc.

Second, we show for \mathcal{H} connected,

$$K_{\mathcal{H}} \text{ homologically acyclic} \not\Rightarrow \chi(K_{\mathcal{H}}) = 1. \quad (16)$$

To see that (16) holds, observe that for a given complex K , we can define \mathcal{N} as the vertex set of K and we can define an edge set \mathcal{E} by: $E \in \mathcal{E}$ when $E \subset \mathcal{N}$ and the vertices in E span a simplex of K . Then the hypergraph $\mathcal{H}_K = (\mathcal{N}, \mathcal{E})$ has K as an associated complex (if \mathcal{E} contains only those subsets that span maximal simplices of K , then \mathcal{H} would be reduced).

So for \mathcal{H} connected (whence $K_{\mathcal{H}}$ connected), (16) is an instance of

$$K \text{ homologically acyclic} \not\Rightarrow \chi(K) = 1 \quad (17)$$

for a connected complex K . But (17) is well known: Identify one point of a 2-sphere with one point of a 1-sphere (circle) and let K be a triangulation of this quotient. Then

$$\chi(K) = \sum_p b_p(K) = b_0 - b_1 + b_2 = 1 - 1 + 1 = 1$$

but K is not homologically acyclic.

Since the first two simple statements of (14) are not equivalent, but the first implies the second, the concept of acyclicity in homology induces a new degree of acyclicity for hypergraphs.

More precisely, call a hypergraph h -acyclic when an associated complex has each of its connected components homologically acyclic. With this definition we have the following degrees of acyclicity for (not necessarily connected) hypergraphs:

$$\text{Berge-acyclic} \Rightarrow \gamma\text{-acyclic} \Rightarrow \beta\text{-acyclic} \Rightarrow \alpha\text{-acyclic} \Rightarrow h\text{-acyclic.} \quad (18)$$

And each of the implications in (18) is (in general) not reversible.

REMARKS

In recent years, much research has been devoted to the study of θ -acyclic ($\theta = \alpha, \beta, \gamma$, Berge) relational database schemes. It has been shown that such schemes enjoy certain desirable properties, e.g., they have monotone join expressions. Because of their utility, the recognition of such schemes is an important design issue and elaborate recognition algorithms have been developed to assist in this capacity. As a fundamental application of our research, we note that since the Euler-Poincaré invariant is readily calculated for the simplicial complex associated with any relational database scheme, it may be used along with the contrapositive forms of Corollaries 10 and 12 to easily determine if a database scheme is not acyclic.

We define an h -acyclic database scheme as one having an h -acyclic hypergraph as its scheme model and observe that an arbitrary database scheme can be made h -acyclic by including an identical attribute in each relation. This follows since the resulting scheme has a cone as its associated simplicial complex and is thus homologically trivial.

A cover of a simplicial complex K is a family of subcomplexes $\mathcal{L} = \{L_\alpha \mid \alpha \in A\}$ with $K = \bigcup_\alpha L_\alpha$. \mathcal{L} is an acyclic cover if each L_α and each finite intersection $\bigcap_\alpha L_\alpha$ are homologically trivial. With this, we offer the following conjecture concerning conditions equivalent to h -acyclicity: *Conjecture. Let R be a database scheme. The following conditions on R are equivalent:*

- (1) R is an h -acyclic hypergraph.
- (2) Graham's algorithm [1, p. 484] terminates with a set S such that $C\ell(S)$ is homologically trivial.
- (3) $C\ell(R)$ has an acyclic cover with the running intersection property.

REFERENCES

1. C. Beeri, R. Fagin, D. Maier and M. Yannakakis, *On the Desirability of Acyclic Database Schemes*, J. ACM 30 (1983), 470-513.
2. A. D'Arti and M. Moscarini, *Recognition Algorithms and Design Methodology for Acyclic Database Schemes*, In: P. Kanellaski and F. Preparata, eds.. *Advances in Computing Research*, Vol. 3 (JAI Press, Greenwich, 1986), 43-67.
3. A. D'Arti and M. Moscarini, *On Hypergraph Acyclicity and Graph Chordality*, Information Proc. Letters 29 (1988), 271-274.
4. R. Fagin, *Degrees of Acyclicity for Hypergraphs and Relational Database Schemes*, J. ACM 30 (1983), 514-550.
5. J.G. Hocking and G.S. Young, "Topology," Addison-Wesley, Reading, Massachusetts, 1961.
6. L. Lovász, "Combinatorial Problems and Exercises," North-Holland, New York, NY, 1979.
7. J.R. Munkres, "Elements of Algebraic Topology," Addison-Wesley, Reading, Massachusetts, 1984.
8. J.J. Rotman, "An Introduction to the Theory of Groups," Allyn and Bacon, Boston, Massachusetts, 1984.

DISTRIBUTION

	<u>Copies</u>		<u>Copies</u>
ATTN CODE 3T COMMANDER NAVAL WEAPONS CENTER CHINA LAKE CA 93555-6001	1	ATTN CODE PD 60 INFORMATION MANAGEMENT SYSTEMS PROGRAM DIRECTORATE SPACE AND NAVAL WARFARE SYSTEMS COMMAND WASHINGTON D C 20363-5100	1
ATTN CODE 014 COMMANDER NAVAL OCEAN SYSTEMS CENTER SAN DIEGO CA 91252-5000	1	ATTN INFORMATION SCIENCE AND TECHNOLOGY OFFICE	1
ATTN CODE 101 OFFICER IN CHARGE NEW LONDON LABORATORY DETACHMENT NAVAL UNDERWATER SYSTEMS CENTER NEW LONDON CT 06320	1	DEFENSE ADVANCED RESEARCH PROJECTS AGENCY 1400 WILSON BLVD ROSYLN VA 22201	
ATTN CODE 01B COMMANDER NAVAL AIR DEVELOPMENT CENTER WARMINSTER PA 18974-5000	1	ATTN CODE 5510 WARFARE SYSTEMS AND SENSORS RESEARCH DIRECTORATE NAVY CENTER FOR APPLIED RESEARCH IN ARTIFICIAL INTELLIGENCE NAVAL RESEARCH LABORATORY WASHINGTON D C 20375	1
ATTN CODE 011 OFFICER IN CHARGE ANNAPOLIS LABORATORY DAVID TAYLOR RESEARCH CENTER ANNAPOLIS MD 21402-1198	1	ATTN R E NANCE SYSTEMS RESEARCH CENTER VIRGINIA POLYTECHNIC INSTITUTE & STATE UNIVERSITY BLACKSBURG VA 24061	1
ATTN CODE 30 OFFICER IN CHARGE OFFICE FOR APPLIED TECHNOLOGY OFFICE OF CHIEF OF NAVAL RESEARCH 800 N QUINCY ST ARLINGTON VA 22204	1	DEFENSE TECHNICAL INFORMATION CENTER CAMERON STATION ALEXANDRIA VA 22314	12

DISTRIBUTION (CONTINUED)

	<u>Copies</u>		<u>Copies</u>
ATTN GIFT AND EXCHANGE		U	1
DIVISION	4	U04	1
LIBRARY OF CONGRESS			
WASHINGTON DC 20540			

INTERNAL DISTRIBUTION

C	1
D	1
D2	1
D4	1
E231	3
E32 GIDEP	1
G	1
H	1
J	1
K	1
K02 FALLIN	1
K07 HUGHEY	1
K10	1
K104 FELL, DIDONATO	2
K106 BLANTON	1
K107 HILL	1
K12	1
K13	1
K13 PARKS	25
K14	1
K40	1
K50	1
N	1
N35 TATE, RIEDL	2
N305 GREEN	1
R	1
R04	1
R44 SZU	1
R44 ZIEN	1

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302 and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE June 1991		3. REPORT TYPE AND DATES COVERED Final
4. TITLE AND SUBTITLE Homology and Hypergraph Acyclicity: A Combinatorial Invariant for Hypergraphs			5. FUNDING NUMBERS	
6. AUTHOR(S) A.D. Parks and S.L. Lipscomb				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Naval Surface Warfare Center (K13) Dahlgren, VA 22448-5000			8. PERFORMING ORGANIZATION REPORT NUMBER NAVSWC TR 91-323	
9. SPONSORING/MONITORING AGENCY NAME(S) AND			10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The natural associations from finite hypergraphs and simple graphs to finite simplicial complexes are used to produce new hypergraph and graph invariants. This correspondence shows that α -acyclic hypergraphs and chordal graphs map to homologically acyclic complexes. A new degree of hypergraph acyclicity (h -acyclicity where the h keys homology) is introduced. It is shown that α -acyclic \Rightarrow h -acyclic, and an example is given to show that this implication is not reversible. Application of these results to database design is discussed and a conjecture characterizing h -acyclic database schemes is stated.				
14. SUBJECT TERMS Database Theory, Hypergraphs, Acyclicity, Euler-Poincaré Formula			15. NUMBER OF PAGES 18	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT SAR	

GENERAL INSTRUCTIONS FOR COMPLETING SF 298

The Report Documentation Page (RDP) is used in announcing and cataloging reports. It is important that this information be consistent with the rest of the report, particularly the cover and its title page. Instructions for filling in each block of the form follow. It is important to *stay within the lines* to meet *optical scanning requirements*.

Block 1. Agency Use Only (Leave blank).

Block 2. Report Date. Full publication date including day, month, and year, if available (e.g. 1 Jan 88). Must cite at least the year.

Block 3. Type of Report and Dates Covered. State whether report is interim, final, etc. If applicable, enter inclusive report dates (e.g. 10 Jun 87 - 30 Jun 88).

Block 4. Title and Subtitle. A title is taken from the part of the report that provides the most meaningful and complete information. When a report is prepared in more than one volume, repeat the primary title, add volume number, and include subtitle for the specific volume. On classified documents enter the title classification in parentheses.

Block 5. Funding Numbers. To include contract and grant numbers; may include program element number(s), project number(s), task number(s), and work unit number(s). Use the following labels:

C - Contract	PR - Project
G - Grant	TA - Task
PE - Program Element	WU - Work Unit Accession No.

BLOCK 6. Author(s). Name(s) of person(s) responsible for writing the report, performing the research, or credited with the content of the report. If editor or compiler, this should follow the name(s).

Block 7. Performing Organization Name(s) and address(es). Self-explanatory.

Block 8. Performing Organization Report Number. Enter the unique alphanumeric report number(s) assigned by the organization performing the report.

Block 9. Sponsoring/Monitoring Agency Name(s) and Address(es). Self-explanatory.

Block 10. Sponsoring/Monitoring Agency Report Number. (If Known)

Block 11. Supplementary Notes. Enter information not included elsewhere such as. Prepared in cooperation with...; Trans. of...; To be published in... When a report is revised, include a statement whether the new report supersedes or supplements the older report.

Block 12a. Distribution/Availability Statement.

Denotes public availability or limitations. Cite any availability to the public. Enter additional limitations or special markings in all capitals (e.g. NOFORN, REL, ITAR).

DOD - See DoDD 5230.24, "Distribution Statements on Technical Documents."
DOE - See authorities.
NASA - See Handbook NHB 2200.2
NTIS - Leave blank

Block 12b. Distribution Code.

DOD - Leave blank.
DOE - Enter DOE distribution categories from the Standard Distribution for Unclassified Scientific and Technical Reports.
NASA - Leave blank.
NTIS - Leave blank.

Block 13. Abstract. Include a brief (*Maximum 200 words*) factual summary of the most significant information contained in the report.

Block 14. Subject Terms. Keywords or phrases identifying major subjects in the report.

Block 15. Number of Pages. Enter the total number of pages.

Block 16. Price Code. Enter appropriate price code (*NTIS only*)

Block 17.-19. Security Classifications. Self-explanatory. Enter U.S. Security Classification in accordance with U.S. Security Regulations (i.e., UNCLASSIFIED). If form contains classified information, stamp classification on the top and bottom of this page.

Block 20. Limitation of Abstract. This block must be completed to assign a limitation to the abstract. Enter either UL (unlimited or SAR (same as report). An entry in this block is necessary if the abstract is to be limited. If blank, the abstract is assumed to be unlimited.